

Dynacom WQ950ZS 5M IR LED Bullet Camera



- 1/1.8" sony IMX178 CMOS sensör
- 5 Megapixel
- IR LEDs: 42 pcs, IR Range: 40M
- 3.6-11mm Motorized Lens
- Built-in IR-CUT, Low power consumption
- H.264 Video Encoding

Model No.	WQ950ZS
CAMERA	
Sensor	1/1.8" sony IMX178 CMOS
Min. Illumination	Color 0.1Lux/F1.4; B/W 0.001Lux/F1.4
Electronic Shutter	Auto/Manual (1/25~1/10000)
Day/Night	Auto/B/W/Color/EXT ICR switching
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	40M(5X42PCS)
Lens	3.6-11mm Motorized lens
Lens Interface Type	M12
AUDIO/VIDEO COMPRESSION	
Video Compression	H.264
Encoding	Dual-stream; Main stream: Starlight/5.0MP@25fps , 3.0MP/2.0M@30fps
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit Rate	16Kbps-8000Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
Audio Bit rate	64Kbps
Recording	SD Card (up to 64GB)
NETWORK FUNCTION	
Motion Detection	Can set a single detection zone, multi-level sensitivity can be set
Video Mask	Support 4 areas to mask
Screen Capture	Support JPEG format , max. resolution based on encoding resolution
Password Protection	Supported
Character Display	Supported (Channel name, Date)
Alarm Function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile Surveillance	Apple iOS, Android
Protocol	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP
Port Protocol	i8S, ONVIF
INTERFACE	
Analog Video Output	1CH CVBS analog video output
Network Interface	RJ45 10M/100M adaptive
GENERAL	
Operating Conditions	-10°C ~ 55°C / 0% - 90%
IP Grade	IP66
Power Supply	DC12V / POE optional
Power Consumption	<5W (without IR LED)
Dimensions	90 x 270 mm (Ø 3,3 x 7,6 in.) w / Sunshield
Weight	About 940g



WDR



5 MP

