

Reolink

PRO SERIES

RP-PCT8M

SMART 4K 125° VIEW POE DOME CAMERA



Overview

Why RP-PCT8MD?

With High Resolution, **Color Night Vision**, and advanced **AI** features, your security is always under control.

4K 8MP Ultra HD

125° Diagonal Viewing Angle

Color Night Vision

2-Way Audio

IP67 Weatherproof

Smart Event Detection

Contact Us

www.reolink.com

4K

4K UHD

Capture the crucial details of any moment with crisp 4K image quality and unmatched flexibility, even at night



AI Analysis

The algorithm analyzes significant movement patterns, ensuring that you receive alerts. motion detection; person detection; vehicle detection; animal detection



Color Night Vision

Equipped with spotlights, it delivers full-color live feeds day and night. Black & white night vision supported by IR LEDs is also available.



Two-Way Audio & Siren

Built-in microphone & speaker for remote communication. Integrated siren to deter intruders.



Time Lapse

Watch long-term processes like birthdays, plant growth, and construction in an enjoyable short video

Video & Audio

Image Sensor

1/2.7" CMOS sensor

Resolution

3840x2160 (8 megapixels)
@25fps

Lens

f=2.8 F=1.6, with IR cut

Video Compression

H.264/H.265

Field of View

Horizontal: 105°
Vertical: 56°
Diagonal: 125°

Day & Night

IR-cut filter with auto-switching

Color Night Vision

Spotlights: 1pc/4.3W/6500K/700 Lumens

Infrared Night Vision

Up to 30 meters (100ft) (LED: 2pcs/2.8w/850nm)

Audio

Two-way audio

Interface

Power Port

DC 12.0V=2A, <12W

PoE

IEEE 802.3af, 48V, Active

Ethernet

One 10M/100Mbps RJ45

SD Card Slot

Supports Max. 512GB microSD card

Reset Button

YES

Audio In/Out

Built-in microphone and speaker

AI Analysis

Perimeter Intrusion

Region Intrusion Detection

Suspicious Activity

Abandoned Object

Removed Object

Software

Frame Rate

Main stream: 2fps - 25fps
Sub stream: 4fps - 15fps

Code Rate

Main stream: 2048Kbps-9216Kbps
Sub stream: 64Kbps-512Kbps

Browsers Supported

IE, Edge, Chrome, Firefox, Safari

OS Supported

PC: Windows, Mac OS;
Smartphone: iOS, Android

Protocols & Standards

HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, P2P, FTP

User Access

20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 sub-streams & 2 main streams)

Smart Alarm

Motion detection/Human Detection/Vehicle Detection/Animal Detection

Perimeter Protection

Line Crossing Alert/Zone Intrusion Alert/Zone Loitering Alert

Smart Event Detection

Object Removal (beta)
Forgotten Object (beta)

Recording Modes

Motion recording, schedule recording, 24/7 recording

Time Lapse

YES

Work with

Google Assistant/Reolink Cloud (available in some countries)

Working Environment

Operating Temperature

-30°C~55°C

Operating Humidity

10% ~ 90%

Weatherproof

IP67

Mechanical

Dimensions

Φ117.4x103.8mm

Weight

526g

Warranty

Limited Warranty

3-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>.



- 1 . Mount
- 2 . Metal Aluminum Case
- 3 . Spot LED
- 4 . Lens
- 5 . Daylight Sensor
- 6 . IR LED



- 1 . Power Port
- 2 . Reset Button
- 3 . Network
- 4 . Port Cover