

Dynacom WQ2BM 2M Waterproof IP Camera



- 2 Megapixel full HD real time
- Highest resolution 1920*1080
- IR Leds:18 pcs* $\varnothing$ 5mm, IR Range: 20M
- 3.6mm MP Fixed Lens
- Built-in IR-CUT, Low power consumption
- H.264 Video Encoding
- Support Dual-Stream / ONVIF agreement / RTSP browse video in real time

Model No.	WQ2BM
CAMERA	
Sensor	1/2.8" Sony Progressive CMOS
Min. Illumination	0.01 lux@F1.2 (Color)/ 0.001 lux@F1.2 (B/W) / (0 Lux IR LED On)
Electronic Shutter	Manual /Auto (Adjustable, 1/1~1/10000)
Day/Night	True Day / Night with ICR Filter
IR Distance	18pcs* $\varnothing$ 5mm, IR Range: 20M
Lens	3.6 mm Fixed Lens
AUDIO/VIDEO COMPRESSION	
Video Compression	H.264 Video Code, Support dual-stream
Bit Rate (CBR/VBR)	Support 32k-8m adjustable,1-30 fps frame rate adjustable
Effective Pixels	1920×1080
Frame Rate	30fps(1080p)
Gain control	Auto
Text Overlay	Time / Date / Camera / Custom OSD
Contrast	YES
NETWORK FUNCTION	
Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Standard protocol	Onvif 2.0
LAN	1 RJ45 10M / 100M Ethernet Port
PC Client and Browser	IE6.0 and above, Google, Chrome, Mozilla, Firefox, Mac Safari
Mobile phone	iPhone, iPad, Android
Bitrate BW Control	VBR / CBR
Password Levels	Users and Administrator
Operation Function	Support Web setting,OSD,real-time video transmission,support motive detection and IO alarm linkage for front end shortage/Capture/playback/download,Support Central remind and image linkage after motive detection and IO alarm linkage,support MJPEG capture,Support unit client-side remote management software、CS-Smart platform system apply, supply complet development kit of SDK.
GENERAL	
Operating Conditions	-10°C~50°C
Power Supply	DC12V±10%, PoE (802.3 af)
Video Output	1Vp-p composite output (75ohm/BNC)
Alarm Input	1
Alarm Output	1
Dimension	$\varnothing$ 117 x 90 mm ($\varnothing$ 4.6 x 3.6 in)



WDR



2MP

