

Dynacom DN6108P SERIES 8CH 960P/8CH 1080P POE NVR



- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free



Model Number		Dynacom DN6108P
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream		Each channel can set main stream and sub stream
Video Standard		1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps
Monitoring Image Quality		1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
Image Motion Detection		Each screen can set mutiple detection areas and set 6-level sensitivity (IPC Support)
Recording Playback Quality		4ch playback in 4ch 720 mode; 1ch 1080P playback in 4ch 960P/1080P model
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup
Operation Way		Mouse
Local Login		User name and password
Recording Storage		Local HDD, network
External Ports	Video Input	① 8×(1280*720)+sub[640*360]+1Ref.+4Play 8ch 1.0MP IP Camera
		② 8×(1280*960)+sub[640*480]+4Ref.+1Play 8ch 1.3MP IP Camera
		③ 8×(1280*960)+sub[720*576]+2Ref.+1Play 8ch 1.3MP IP Camera
		④ 8×(1920*1080)+sub[640*480]+2Ref.+1Play 8ch 2.0MP IP Camera
		⑤ 8×(1920*1080)+sub[720*576]+1Ref.+1Play 8ch 2.0MP IP Camera
	Audio Input	8ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA Output
	Network Port	9 RJ45, 100M LAN port, data transferring and power supply both by network cable
	USB Port	3 USB 2.0 ports
	Wireless Port	3G, WIFI
HDD	HDD Port	1 SATA HDD Port
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance		Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply		DC48V 2.5A
Power Consumption		≤115W (without HDD)
Working Temperature		-10℃～+55℃
Working Humidity		10%-90%
Dimension		Equipment : 260mm×220mm×43mm, Packing : 355mm×255mm×88.5mm
Weight(without HDD)		N.W. : 1.7Kg ; With packing : 2.6Kg
Outside Carton		10 pcs/carton. 525mm×455mm×365mm ; Weight : 27 Kg
Installation Way		Desktop Installation