

Reolink

HOME HUB PRO

WI-FI 6 WIRELESS SECURITY CENTER WITH CENTRALIZED MANAGEMENT



Overview

Device Management

Camera

Up to 24 cameras

Device Compatibility

All Reolink Wi-Fi & PoE cameras Plug-in Wi-Fi cameras, and PoE cameras

Input / Output

HDMI/USB/Reset Button Ethernet

Yes 1 x RJ-45 10/100 Mbps self-adaptive (for WAN)
Power 1 x RJ-45, 10/100 Mbps self-adaptive (for IP cameras)
Speaker Max.120dB

Storage

SATA

YES (1x2TB HDD included)

microSD Card Slot

Up to 1x512GB (microSD card is unable to save videos when both the HDD and microSD card are inserted.)

Storage Encryption

AES-128 encryption algorithm

Preview & Playback

Live View

App, PC Client

Playback

Smart Playback/Quick Events History

System

Network Protocols

TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP

Max. User Access

11 users (1 admin account & 10 shared accounts)

Working

Environment

Operating Temperature

-10°C ~ 45°C

Operating Humidity

10% ~ 90%

Mechanical

Dimensions

95×95×161.8mm

Weight

441g

Why Home Hub Pro?

Built-in 2TB HDD

Wi-Fi 6 Ready

Up to 24 Reolink Cams Supported

Centralized Data Management

Encrypted Local Storage Without Fees

Contact Us

www.reolink.com

Wi-Fi

Wireless Standard

IEEE 802.11 a/b/g/n/ac/ax (Wi-Fi 6)

Operating Frequency

2.4/5 GHz

Wireless Security

WPA/WPA2/WPA3

SUB-1 GHz

Operating Frequency

868/915MHz