

Industrial Unmanaged Power over Ethernet Switch

4-Ports 10/100Mbps-TX(PoE) + 2-Slots 100Mbps SFP



SFC 300PoE

- 4-Ports 10/100Mbps-TX(PoE)
- 2-Slots 100Mbps SFP
- IEEE 802.3af 15.4Watt PoE
- 2K MAC Address
- Wide operating temperature : -40°C~70°C
- DC 48V

Features

- Support Din-Rail
- Power polarity reverse protect
- Power : DC 48V (Terminal Block)
- IEEE 802.3af 15.4Watt PoE
- Industrial 100Mbps Fiber Optic Converter

Specifications

Technology	- Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX/100Base-FX IEEE 802.3af Power over Ethernet Standards
Interface	- RJ45 Ports	4-Ports 10/100Mbps, Auto MDI/MDI-X UTP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m) Provides DC 48V Power over RJ-45 Ethernet cable to devices with Ethernet port
	- Fiber Ports	100Base-FX, SFP 2-Ports Multi mode: 62.5/125 μ m, 50/125 μ m(220/550m), Single mode: 9/125 μ m(20km~100km)
	- LED Indicators	Per unit: Power, Fault TX Port (Link/Act, FDX/HDX, Speed) FX Port (Link/Act, FDX/HDX, Speed) External DIP : Auto-negotiation, 10/100Mbps, Full/Half Duplex, Fault on/off
Performance	- Data Transfer	100Mbps
	- MAC Address	2K MAC address table
Environmental	- Temperature	Operation: -40°C ~ 70°C, Store: -45°C ~ 85°C
	- Humidity	5% ~ 95% (Non-condensing)
Power Supply	- Input Voltage	DC 48V
Mechanical	- Installation	DIN-Rail, Panel Mounting
	- Dimensions	55mm(W) x 120mm(D) x 150mm(H), 744g