

Premium H.264 IP Camera W7-3x Series



Item		W7-2M/3x	
Camera			
Image Sensor		1/2.8"Sony Progressive CMOS	
Effective Pixels		1920(H) x 1080(V)	
Shutter Speed		1 - 1/10000 sec.	
Lens			
Lens		3x Optical Zoom, Auto Focus	
F Number		F1.2 (Wide); F2.1 (Tele)	
Operation			
Multiple Languages		English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	
Image Setting	Iris Control		P-IRIS & DC-IRIS
	Backlight		On / Off
	White Balance		Manual / AWB / ATW / One Push
	Noise Reduction	3D	On / Off
	Wide Dynamic		On / Off
	Privacy Mask		On / Off
	Brightness		Manual
	Exposure		Auto / Manual
	Sharpness		Manual
	Contrast		Manual
	Saturation		Manual
	Hue		Manual
	Digital Zoom		Support
	Motion detection		On / Off / By Schedule
	Privacy Mask Type		Color
ICR		Auto / On / Off / Smart	
Tampering Alarm		On / Off / By Schedule	
Audio	Two-way Audio		Line out, Line in
	Compression		G.711 / G.726
Network			
Interface		RJ-45, 10/100 Mbps Ethernet	
Video Compression		H.264 (MPEG-4 Part 10/AVC)/ MJPEG	
Video Streaming		Quad Streams H.264 + H.264 + H.264 + MJPEG / H.264 + H.264 + H.264 + H.264	
Video Resolution		H.264- Full HD 1080P / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / HD 720P / XGA / SVGA / D1 / VGA / CIF	
Protocol		IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, ARP, QoS, ONVIF	
Security		HTTPS / IP Filter / IEEE 802.1x	
Alarm	Input	1 Set	
		5V 10KΩ pull up	
	Output	1 Set Photo Relay Output 300V DC/AC	
Event Notification		HTTP / FTP / SMTP	
Micro SD		microSDHC 32GB support	
User Account		20	
Password Levels		User and Administrator	
Internet Browser		Internet Explorer (6.0+), Chrome, Firefox, Safari	
Mechanical			
LED Indicator		Power / Link / ACT	
Connectors	Alarm	4 Pin Terminal Block	
	Power	3 Pin Terminal Block	
	Ethernet	RJ-45	
	Analog Video	1.0 Vp-p / 75 Ω, BNC	
	RS-485	D+, D-	
	Audio	Stereo Phone Jack, Ø 3.5 mm	
General			
Operating Temperature		-10° C ~ 50° C (14° F~122° F)	
Humidity		10% ~ 90%, No Condensation	
Dimension		165.0 x 80.0 x 52.4 mm (L x W x H)	
Weight		300 g (0.66 lb)	
Power Source		DC 12V /AC 24V / PoE	
Power Consumption		6 W (500 mA)	
Regulatory		CE / FCC / RoHS	

* mark for optional items

Product specification and availability are subject to change without notice.